DMX

EUROLITE AT-DIMM 8 DMX Dimmer DC 24V/6A

8-channel dimmer for 24 V operation

- DMX dimmerpack
- Power 6 A, 24 V DC
- 8 separately adjustable channels
- Control unit with LCD
- 13 built-in programs

No. 70064176

Technical specifications:

Power supply:	230 V AC, 50 Hz
Max. power output:	144 W
Output voltage:	24 V DC
Max. output:	6 A
DMX control channels:	6, 9, 15, 24, or 27
Integrated programs:	13
DMX output:	3-pin female XLR socket
DMX input:	3-pin male XLR socket
Dimensions (WxDxH):	350 x 230 x 75 mm
Weight:	3 kg

EUROLITE LCD-4/S Dimmer controller

4-channel lighting controller

- 4 channels
- LED display of all modes
- 42 built-in programs



No. 70062661

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Max. power output:	3680 W
Max. current:	16 A
Number of control channels:	4
Max. output/channel:	1150 W
Max. current/channel:	5 A
Integrated programs:	42
Sound-control:	via built-in microphone or via audio-input
Audio-input:	RCA socket
Audio-sensitivity:	0.1 - 1 V
Output sockets:	4 safety sockets
Fuse:	4 x F 6,3A, 250 V
Dimensions (WxDxH):	482 x 145 x 132 mm
	Rack installation with 3 u
Minimum mounting depth:	230 mm
Weight:	4.5 kg

EUROLITE MINI-4B Box version

For wall mounting

- Connection via 4 IEC output sockets
- Adjustable speed
- 4 channels



No. 70062606

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Max. power output:	1,150 W
Max. current:	5 A
Number of control channels:	4
Max. output/channel:	1,150 W
Max. current/channel:	5 A
Sound-control:	via built-in microphone
Output sockets:	Four IEC-output-sockets
Fuse:	F 6.3 A, 250 V
Dimensions (WxDxH):	240 x 200 x 60 mm
Weight:	1 kg

USB

FUTURELIGHT ULB-2 USB upload box

Upload box for fixture software upgrades

- Upload box for fixture software upgrades

No. 51836903

Technical specifications:

Power supply:	5 V DC