EUROLITE FS-600/ Spot GKV-600

600 W GKV-600 stage spotlight

- Aluminum housing
- Lens with 19°/26°/36°/50° beam angle
- Ideal for theatres as pre-stage spot

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption:	600 W
Weight:	6 kg
Dimensions:	540 x 240 x 390 mm

No. 40002500 ..... 19°, black
No. 40002501 ..... 19°, silver
No. 40002510 ..... 26°, black
No. 40002511 ..... 26°, silver
No. 40002520 ..... 36°, black
No. 40002521 ..... 36°, silver
No. 40002530 ..... 50°, black
No. 40002531 ..... 50°, silver

No. 40002701

EUROLITE Gobo holder for FS-600 spot bk

Gobo holder

- Diameter 80 mm

EUROLITE TVS-800 TV and studio spot 800W

Compact spot

- Including protective grille
- Stable mounting bracket
- High light output

No. 41907220

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption:	800 W
Dimensions (LxW):	220 x 220 mm
Weight:	1.5 kg

DMX COB DAYLIGHT

EUROLITE LED STL-50F COB 5600K

Daylight studio lighting with powerful 50 W COB LED

- With Fresnel lens
- 5600 K color temperature
- Functions: dimmer, strobe effect, Master/Slave operation
- Manually adjustable zoom
- With color filter frame

No. 41602580

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption:	65 W/105 VA
DMX control channels:	1/3
DMX512 connection:	3-pin XLR
Type of LEDs:	Array 50 W
Number of LEDs:	1
Color temperature:	5600 K
Beam angle:	7° - 36°
Dimensions (LxWxH):	280 x 240 x 320 mm
Weight:	4.5 kg

NEW DMX COB CW + WW

EUROLITE LED SFR-100 COB CW/WW 100W Floor

Silent COB spot with 100 W LED in cold and warm white

- Convection cooling entirely via cooling ribs, no fans, particularly quiet
- Flicker-free projection
- Dimmer speed (step response) adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Beam angle 35°

No. 41607600

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz ~
Power consumption:	90 W
DMX control channels:	4
DMX512 connection:	3-pin XLR
Flash-rate:	17 Hz
Number of LEDs:	1
LED type:	Array Cluster 100 W, CW/WW
Color temperature:	2900-6000 K
Beam angle:	35°
Dimensions (LxWxH):	290 x 270 x 285 mm
Weight:	6.5 kg

Delivery, technical changes, errors and omissions exempted. Please take notice of the user manuals and latest information which can be downloaded from our site. All pictures are similar and partially symbolic.